



**Advanced Coating Technologies**

**Item:** *SLPK10173*

**Description:** *92# PK Liner Super Lay Flat*

**Shelf Life (in months):** *12*

Strata-Tac will warrant the release of its products as long as the release liner is converted on or before the 'Best Used by Date.

**Storage Requirements:**

Strata-Tac suggests that the release liner once received be stored in conditions as outlined below:

- Temperature 40F – 90F (4C – 32C)
- Relative Humidity 40% - 60%

**Product Line:**

The super layflat products from Strata-Tac are generally polycoated on two sides and silicone coated on one side. They provide excellent smoothness and layflat characteristics.

**Release Liners to Meet Your Needs:**

*Clean (No fiber dust)*

*Dimensionally stable*

*Good die cut surface*

*Polypropylene resin for heat resistance*

*High density; able to withstand higher temperatures*

<u>Characteristic</u>	<u>Strata-Tac Reports As</u>	<u>Target</u>	<u>UOM</u>	<u>Tappi Equivalent</u>
Basis Weight	LTM-0005	92.00	lb/ream	Tappi-410
Caliper	LTM-0009	6.8	mils	Tappi-411
Release	LTM-0156	85	g/in	
Tear CD	LTM-0074	115	gf	Tappi T-414
Tear MD	LTM-0075	105	gf	Tappi T-414
Tensile CD	LTM-0076	28	lb/in	Tappi T-494
Tensile MD	LTM-0078	50	lb/in	Tappi T-494

*This Product Data Sheet is an uncontrolled document and the target values presented are those in place at the time of printing. The information should be used as a guideline only. This information does not represent ranges or values that should be used for the generation of a specification.*

3/30/2015