

Description

Typical Performance Properties

| | |
|---|--|
| 180° Peel to Stainless Steel (lb./in.) (15 min) | |
| 180° Peel to Stainless Steel; (lb./in.) (24 hour) | |
| | |
| | |
| PSTC-16, Looptack (lb./in.) | |
| | |
| | |
| PSTC-107, Shear Adhesion 1" x 1" x 1,000 grams) | |

Features

Typical Adhesive Properties

| | |
|---------------------------------|--|
| Minimum Application Temperature | |
| Service Temperature Range | |

Popular Product Uses

FDA Compliance

Additional Information

Notice: All statements, technical information and recommendations about Strata-Tac products are based on information believed to be reliable. They are offered in good faith but do not constitute a guarantee or warranty, as conditions and methods of use of our products are beyond our control. Strata-Tac makes no warranties either express or implied, of merchantability, or fitness for a particular purpose of any nature with respect to information or the product to which this information refers. We recommend that the prospective user determines the suitability of our materials in potential applications prior to use. Information contained herein is not to be understood as recommendation to use any product, process, equipment or formulation in conflict with any patent, nor as permission or license to use any patents of Strata-Tac. All terms related to the purchase of this product will be as set forth in Strata-Tac's standard Terms and Conditions of Sale.