

**SAFETY DATA SHEET**

Revision Date: 01/07/2017

Print Date: 2/20/2017

SDS Number: 000000119256

Version: 1.4

**#602 All Temp Perm Adhesive**

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

**Relevant identified uses of the substance or mixture and uses advised against**

<p><b>Details of the supplier of the safety data sheet</b>          Strata-Tac Inc.          3980 Swenson Ave          Saint Charles, IL 60174          United States of America (USA)          630-879-9388</p> <p>customerservice@stratatac.com</p>	<p><b>Emergency telephone number</b>          1-800-884-9388</p> <p><b>Regulatory Information Number</b>          1-800-884-9388</p> <p><b>Product Information</b>          800-884-9388</p>
---	--


**SECTION 2. HAZARDS IDENTIFICATION**

**GHS Classification**

Carcinogenicity : Category 1B

Reproductive toxicity : Category 2

**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : May cause cancer.  
 Suspected of damaging fertility or the unborn child.

Precautionary Statements : **Prevention:**  
 Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and

<b>SAFETY DATA SHEET</b>		Revision Date: 01/07/2017
		Print Date: 2/20/2017
		SDS Number: 000000119256
		Version: 1.4

understood.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

IF exposed or concerned: Get medical advice/ attention.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	Carc. 1B; H350 Repr. 2; H361 STOT RE 1; H372 Asp. Tox. 1; H304	0.2245
VINYL ACETATE MONOMER	108-05-4	Flam. Liq. 2; H225 Acute Tox. 4; H332 Carc. 2; H351 STOT SE 3; H335	0.2137

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.

<b>SAFETY DATA SHEET</b>		Revision Date: 01/07/2017
		Print Date: 2/20/2017
		SDS Number: 000000119256
		Version: 1.4

If inhaled	: If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	: Obtain medical attention. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: May cause cancer. Suspected of damaging fertility or the unborn child. No symptoms known or expected.
Notes to physician	: No hazards which require special first aid measures.

---

## SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known
Specific extinguishing methods	:

<b>SAFETY DATA SHEET</b>		Revision Date: 01/07/2017
		Print Date: 2/20/2017
		SDS Number: 000000119256
		Version: 1.4

Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

---

## SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.  
Do not smoke.  
Container hazardous when empty.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

		Revision Date: 01/07/2017
<b>SAFETY DATA SHEET</b>		Print Date: 2/20/2017
		SDS Number: 000000119256
		Version: 1.4

Protect from frost.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
		VINYL ACETATE MONOMER	108-05-4	TWA
	STEL	15 ppm		ACGIH
	C	4 ppm 15 mg/m3		NIOSH REL
	TWA	10 ppm 30 mg/m3		OSHA P0
	STEL	20 ppm 60 mg/m3		OSHA P0
	PEL	10 ppm 30 mg/m3		CAL PEL
	STEL	15 ppm 45 mg/m3		CAL PEL

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

### Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate

**SAFETY DATA SHEET**

Revision Date: 01/07/2017

Print Date: 2/20/2017

SDS Number: 000000119256

Version: 1.4

cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

- Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
- Skin and body protection : Wear as appropriate:  
Impervious clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Wash hands before breaks and at the end of workday.  
When using do not eat or drink.  
When using do not smoke.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Physical state : liquid
- Colour : white
- Odour : sweet
- Odour Threshold : No data available
- pH : 5
- Melting point/freezing point : No data available
- Boiling point/boiling range : > 212 °F / 100 °C

**SAFETY DATA SHEET**

Revision Date: 01/07/2017

Print Date: 2/20/2017

SDS Number: 000000119256

Version: 1.4

666140

Flash point	: > 93.4 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: 24.8 hPa (21 °C)
Relative vapour density	: No data available
Relative density	: No data available
Density	: 1.01 g/cm <sup>3</sup> (21 °C)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Oxidizing properties	: No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	: Product will not undergo hazardous polymerization.

**SAFETY DATA SHEET**

Revision Date: 01/07/2017

Print Date: 2/20/2017

SDS Number: 000000119256

Version: 1.4

Hazardous decomposition  
products

No hazardous decomposition products are known.

**SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

**Acute toxicity**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: Not classified as acutely toxic by inhalation under GHS.  
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Remarks: No mortality observed at this dose.

**VINYL ACETATE MONOMER:**

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 15,810 mg/m<sup>3</sup>  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit, male): 7,440 mg/kg  
GLP: no

**Skin corrosion/irritation**

Not classified based on available information.

**Components:**

**DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:**

Species: Rabbit

Result: No skin irritation

**VINYL ACETATE MONOMER:**

Species: Rabbit



<b>SAFETY DATA SHEET</b>		Revision Date: 01/07/2017
		Print Date: 2/20/2017
		SDS Number: 000000119256
		Version: 1.4

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: yes

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks: Unlikely to cause eye irritation or injury.

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Species: Rabbit

Result: No eye irritation

VINYL ACETATE MONOMER:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: yes

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

VINYL ACETATE MONOMER:

Test Type: Local lymph node assay

Species: Mouse

Method: OECD Test Guideline 429

Result: Did not cause sensitisation on laboratory animals.

GLP: yes

Germ cell mutagenicity

Not classified based on available information.

**Components:**

VINYL ACETATE MONOMER:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
 Test species: Human lymphocytes  
 Method: OECD Test Guideline 473  
 Result: positive

: Test Type: Ames test  
 Metabolic activation: with and without metabolic activation

**SAFETY DATA SHEET**

Revision Date: 01/07/2017

Print Date: 2/20/2017

SDS Number: 000000119256

Version: 1.4

Method: OECD Test Guideline 471

Result: negative

- : Test Type: Ames test  
Metabolic activation: Metabolic activation  
Method: Mutagenicity (Escherichia coli - reverse mutation assay)  
Result: negative
- : Test Type: Micronucleus test  
Test species: human lymphoblastoid cells  
Result: positive

**Carcinogenicity**

May cause cancer.

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Carcinogenicity - Assessment : Sufficient evidence of carcinogenicity in animal experiments

VINYL ACETATE MONOMER:

Carcinogenicity - Assessment : Limited evidence of a carcinogenic effect.

**Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

VINYL ACETATE MONOMER:

Effects on fertility :

- Test Type: Two-generation study
- Species: Rat
- Sex: male and female
- Application Route: Oral
- NOAEL: 100 mg/kg,
- F1: 100 mg/kg,
- F2: 100 mg/kg,
- Method: OECD Test Guideline 416
- GLP: yes

Effects on foetal development :

- Species: Rat, females
- Application Route: Oral
- 477 mg/kg
- GLP: yes
- Species: Rat, females

**SAFETY DATA SHEET**

Revision Date: 01/07/2017

Print Date: 2/20/2017

SDS Number: 000000119256

Version: 1.4

Application Route: Inhalation  
 205 mg/kg  
 GLP: yes

**STOT - single exposure**

Not classified based on available information.

**Components:**

VINYL ACETATE MONOMER:

Assessment: May cause respiratory irritation.

**STOT - repeated exposure**

Not classified based on available information.

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Exposure routes: Skin contact

Target Organs: Adrenal gland

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: Bone marrow

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: Liver

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: Kidney

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: Immune system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: thymus gland

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Exposure routes: Skin contact

Target Organs: Stomach

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

**SAFETY DATA SHEET**

Revision Date: 01/07/2017

Print Date: 2/20/2017

SDS Number: 000000119256

Version: 1.4

**Repeated dose toxicity****Components:**

VINYL ACETATE MONOMER:

Species: Mouse, female

NOAEL: 281 mg/kg

Application Route: Oral

Exposure time: 90-day

Method: OECD Test Guideline 408

GLP: yes

Species: Mouse, male

NOAEL: 285 mg/kg

Application Route: Oral

Exposure time: 90-day

Method: OECD Test Guideline 408

GLP: yes

Species: Rat, female

NOAEL: 810 mg/kg

Application Route: Oral

Exposure time: 90-day

Method: OECD Test Guideline 408

GLP: yes

Species: Rat, male

NOAEL: 684 mg/kg

Application Route: Oral

Exposure time: 90-day

Method: OECD Test Guideline 408

GLP: yes

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration toxicity classification

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

**Further information****Product:**

Remarks: No data available

**SAFETY DATA SHEET**

Revision Date: 01/07/2017

Print Date: 2/20/2017

SDS Number: 000000119256

Version: 1.4

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 203  
 Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
 Exposure time: 48 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
 End point: Growth inhibition  
 Exposure time: 72 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l  
 Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l  
 Exposure time: 21 d  
 Test substance: WAF  
 Method: OECD Test Guideline 211

**VINYL ACETATE MONOMER:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 14 mg/l  
 Exposure time: 96 h  
 Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 12.6 mg/l  
 Exposure time: 48 h  
 Test Type: static test  
 Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (microalgae)): 12.7 mg/l

**SAFETY DATA SHEET**

Revision Date: 01/07/2017

Print Date: 2/20/2017

SDS Number: 000000119256

Version: 1.4

Exposure time: 72 h  
 Method: OECD Test Guideline 201  
 GLP: yes

Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 0.16 mg/l  
 Exposure time: 34 d  
 Test Type: flow-through test  
 Method: OECD Test Guideline 210

No data available

**Persistence and degradability****Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Biodegradability : Result: Not readily biodegradable.  
 Biodegradation: 2 - 4 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301B

VINYL ACETATE MONOMER:

Biodegradability : Inoculum: activated sludge  
 Result: Readily biodegradable.  
 Biodegradation: 82 - 92 %  
 Exposure time: 14 d  
 Method: OECD Test Guideline 301C

No data available

**Bioaccumulative potential****Components:**

VINYL ACETATE MONOMER:

Bioaccumulation : Bioconcentration factor (BCF): 3.16  
 Method: see user defined free text

Partition coefficient: n-octanol/water : log Pow: 0.73

No data available

**Mobility in soil****Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : No data available

**Components:**

<b>SAFETY DATA SHEET</b>		Revision Date: 01/07/2017
		Print Date: 2/20/2017
		SDS Number: 000000119256
		Version: 1.4

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

- General advice : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.
- Dispose of in accordance with all applicable local, state and federal regulations.
- Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Do not re-use empty containers.

---

## SECTION 14. TRANSPORT INFORMATION

### International transport regulations

#### REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

#### MX\_DG

Not dangerous goods

#### INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

#### INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

#### INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

#### TDG\_INWT\_C

Not dangerous goods

**SAFETY DATA SHEET**

Revision Date: 01/07/2017

Print Date: 2/20/2017

SDS Number: 000000119256

Version: 1.4

**TDG\_RAIL\_C**

Not dangerous goods

**TDG\_ROAD\_C**

Not dangerous goods

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods

**CFR\_RAIL\_C**

Not dangerous goods

**U.S. DOT - ROAD**

Not dangerous goods

**\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant

no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION****SARA 311/312 Hazards** : Chronic Health Hazard**SARA 313**VINYL ACETATE  
MONOMER

108-05-4

0.21 %

**California Prop 65**WARNING! This product contains a chemical known to the  
State of California to cause cancer.

ACETALDEHYDE

75-07-0

BENZENE

71-43-2



**SAFETY DATA SHEET**

Revision Date: 01/07/2017

Print Date: 2/20/2017

SDS Number: 000000119256

Version: 1.4

1,4-DIOXANE 123-91-1

ETHYLENE OXIDE 75-21-8

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

BENZENE 71-43-2

ETHYLENE OXIDE 75-21-8

**The components of this product are reported in the following inventories:**

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

**SECTION 16. OTHER INFORMATION****Further information**

Revision Date: 01/07/2017

**NFPA:****HMIS III:**


**SAFETY DATA SHEET**

Revision Date: 01/07/2017

Print Date: 2/20/2017

SDS Number: 000000119256

Version: 1.4

**NFPA Flammable and Combustible Liquids Classification**

Combustible Liquid Class IIIB Combustible Liquid Class IIIB

**Full text of H-Statements**

H225	Highly flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure in contact with skin.

Sources of key data used to compile the Safety Data Sheet

Ashland internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

<b>SAFETY DATA SHEET</b>		Revision Date: 01/07/2017
		Print Date: 2/20/2017
		SDS Number: 000000119256
		Version: 1.4

ACGIH : American Conference of Industrial Hygienists  
 BEI : Biological Exposure Index  
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
 FG : Food grade  
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
 H-statement : Hazard Statement  
 IATA : International Air Transport Association.  
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
 IMDG : International Maritime Code for Dangerous Goods  
 ISO : International Organization for Standardization  
 logPow : octanol-water partition coefficient  
 LCxx : Lethal Concentration, for xx percent of test population  
 LDxx : Lethal Dose, for xx percent of test population.  
 ICxx : Inhibitory Concentration for xx of a substance  
 Ecxx : Effective Concentration of xx  
 N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT : Department of Transportation  
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
 HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health  
 OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System