

Adhesive Choices for Your Application



Strata-Tac offers a wide range of adhesives to fit most any application. Strata-Tac offers water based acrylic adhesives in permanent, removable and ultra-removable. We have adhesive options that are skin safe, blood bag compliant, and usable for direct and indirect food contact as well as BS5609 certified.

Adhesive ID	Service Temp Range	Min App Temp	Loop Tack (SS)	15min Peel (SS)	Shear (SS)	Description
Permanent	601	-18F to +135F	+20F	1.7 lb/in	2.0 lb/in	36 hrs. A general purpose acrylic adhesive with good initial tack, high shear and ultimate adhesion. 601 is approved for indirect food and is also a repulpable adhesive.
	610 E	-40F to +250F	+35F	3.8 lb/in	3.5 lb/in	4 hrs. Durable, outdoor, marine-grade permanent adhesive. Good performance on tight mandrel applications. ISO10993 Skin safe, BS5609 and indirect food approved.
	616 D	-65F to +200F	+25F	7.0 lb/in	7.0 lb/in	50 hrs. High shear water-based acrylic permanent adhesive. Can be used as a solvent replacement. High solids means a higher coat weight. Excellent for low energy surfaces and tight mandrel applications.
	617 B	-50F to +125F	-10F	3.6 lb/in	2.7 lb/in	11 hrs. All-temp adhesive with good high speed convertibility, excellent low temperature performance and rapid wet out.
	619 G	-65F to +200F	-20F	2.5 lb/in	1.5 lb/in	1 hr. High shear adhesive for indoor/outdoor use. Rated for BS5609 drum label applications. Blood bag compliant.
	626 U	-40 to +250F	+15F	3.5 lb/in	3.1 lb/in	30 hrs. Combines excellent adhesion with good cohesion, which allows high and low energy surface applications. Great for tight mandrel applications. Very water resistant; BS5609 & UL #969 and ISO10993 skin safe compliant.
Removable	614 Q	-65F to +250F	-10F	1.5 lb/in	1.2 lb/in	1.7 hrs. Mid-tack all temp removable. FDA approved for direct food contact. Blood bag compliant and ISO:10993 skin safe compatible. It also performs excellent as a shelf marking adhesive.
	611	-18F to +135F	+40F	1.7 lb/in	2.0 lb/in	36 hrs. Mid-tack removable adhesive. Excellent for shelf labels or other applications when clean removability is a must.
	622 T	-50F to +135F	0F	2.8 lb/in	1.2 lb/in	24 hrs. General purpose removable exhibiting excellent adhesion to polyester, BOPP, and paper face stocks.
	630 QA	-40F to +250F	+40F	1.3 lb/in	1.5 lb/in	24 hrs. Plasticizer-resistant removable adhesive for compatibility with PVC films. Low peel provides excellent removability from a wide variety of surfaces. Great for shelf-talkers, window decals, and more.
Ultra-Removable	604 R	-20F to +220F	+35F	0.5 lb/in	0.1 lb/in	1 hr. Ultra removable "cling" adhesive with excellent removability from glass. Use for window decals, oil change labels, or as a vinyl cling substitute. Approved for indirect food labeling.
	605 Y	+20F to 250F	+32F	0.8 lb/in.	0.5 lb/in	Microsphere adhesive designed for re-positionable applications. Approved for indirect food contact.

Notice: All statements, technical information and recommendations about Strata-Tac products are based on information believed to be reliable. They are offered in good faith but do not constitute a guarantee or warranty, as conditions and methods of use of our products are beyond our control. Strata-Tac makes no warranties either express or implied, of merchantability, or fitness for a particular purpose of any nature with respect to information or the product to which this information refers. We recommend that the prospective user determines the suitability of our materials in potential applications prior to use. Information contained herein is not to be understood as recommendation to use any product, process, equipment or formulation in conflict with any patent, nor as permission or license to use any patents of Strata-Tac. All terms related to the purchase of this product will be as set forth in Strata-Tac's standard Terms and Conditions of Sale.

If you don't see an adhesive that meets your needs contact us by visiting www.stratatac.com/contact