



Material Safety Data Sheet

Strata-Tac WHITE POLYESTER FILM

Issue Date: December 1, 2000

Revised: June 3, 2013

Emergency Contact

For Emergency Call 1-800-884-9388

Product Identification

This MSDS applies to white opaque Strata-Tac polyester base films used to make top coated and/or adhesive coated label products. These products are polyethylene terephthalate (CAS# 25038-59-9) containing barium sulfate (CAS# 7727-43-7).

Hazardous Ingredients

Low levels of Acetaldehyde (CAS# 75-07-0) are present in the film. Under normal use conditions, release would be negligible.

Established exposure limits for acetaldehyde in the U.S. are:

ACGIH TLV = 25 ppm (ceiling)

OSHA PEL = 200 ppm TWA

The film also contains Barium Sulfate immobilized in the polymer matrix. Under normal use conditions, exposure is not expected. However, machining, grinding, or other dusting conditions should be monitored and respirable dust and particulate exposure maintained below established exposure limits.

Established exposure limits for barium sulfate in the U.S. are:

ACGIH TWA = 10 mg/m³

OSHA PEL = 5 mg/m³ (respirable fraction)

= 15 mg/m³ (total dust)

Physical-Chemical Data

The white, odorless film is chemically stable and resistant to attack by oils, solvents, weak acids and weak alkalis. The film melts at 250°C and decomposes at temperatures above 250°C. It has a specific gravity of 1.4 - 1.5.

Physical Hazards

Heavy gauges of polyester film can contain sharp edges. Proper protective gear, such as gloves, is recommended.

Unwinding, winding and passage of polyethylene terephthalate film through and over rollers will tend to generate a strong electrostatic charge on the web. Static discharge devices should be properly positioned at such points to eliminate the charge and to prevent uncontrolled discharge from the web. This is particularly required in potentially explosive atmospheres and to protect personnel from the effect of a static discharge.

Health Hazard Data

No adverse health effects have been attributed to polyester film.

Hazard Designations

KEY

	<u>NFPA</u>	
Health:	0	0-None
Flammability:	1	1-Slight
Reactivity:	0	2-Moderate
		3-Severe
		4-Extreme

Control Measures and Safe Handling Procedures

The film will burn if exposed to flame. Fire fighters should protect themselves from hazardous decomposition and combustion products that may include acetaldehyde, carbon monoxide and other toxic gases. Wear self-contained breathing apparatus and complete personal protective equipment when potential for exposure to products of combustion exists. Fire fighting extinguishing media include carbon dioxide, water spray, foam or dry chemical.

If the film could be subjected to conditions releasing acetaldehyde, then adequate ventilation should be used to stay below the established exposure limits, or self-contained breathing apparatus should be used.

Disposal and Shipping Information

Polyester film is not classified as a hazardous waste under the Resource Conservation And Recovery Act and, unless prohibited by state or local regulation, can be disposed of in a municipal landfill or incinerated.

This product is not classified by the Department of Transportation as a hazardous material.

Regulatory

U.S. Regulations

This product is classified as an article under the TSCA.
State RTK - MA, PA (Barium Sulfate, 7727-43-7)
No components are listed on SARA 313.

Canada and Europe

Polyethylene terephthalate polymer is listed on the Canadian DSL and its reactants are listed on EINECS.

Information Contact

Strata-Tac, Inc.
Environmental, Safety, and Health
Affairs 3980 Swenson Ave
Saint Charles, IL. 60174
630-879-9388

Judgments as to the suitability of information herein are the purchaser's responsibility. Although reasonable care has been taken in the preparation of such information, Strata-Tac, Inc. extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information to the purchaser's intended purpose or for consequences of its use.